

# UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No.

35.C.13518

First Named Inventor or Application Identifier

JUNICHI SEKI

Express Mail Label No.

## APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

## ADDRESS TO:

Assistant Commissioner for Patents  
Box Patent Application  
Washington, DC 20231

Fee Transmittal Form

(Submit an original, and a duplicate for fee processing)

2. ☒ X

Specification

Total Pages 38

3. ☒ X

Drawings(s) (35 USC 113)

Total Sheets 22

4. ☒ X

Oath or Declaration

Total Pages 1

a. ☐

Newly executed (original or copy)

b. ☒ X

Unexecuted for information purposes

c. ☐

Copy from a prior application (37 CFR 1.63(d))  
(for continuation/divisional with Box 17 completed)

(Note Box 5 below)

i. ☐

DELETION OF INVENTOR(S)

Signed Statement attached deleting inventor(s) named in  
the prior application, see 37 CFR 1.63(d)(2) and 1.33(b).

☐ Incorporation By Reference (assessable if Box 4c is checked)

The entire disclosure of the prior application, from which a copy of the oath or  
declaration is supplied under Box 4c, is considered as being part of the disclosure of  
the accompanying application and is hereby incorporated by reference therein.

6. ☐

Microfiche Computer Program (Appendix)

7. Nucleotide and/or Amino Acid Sequence Submission  
(if applicable, all necessary)

a. ☐

Computer Readable Copy

b. ☐

Paper Copy (identical to computer copy)

c. ☐

Statement verifying identity of above copies

## ACCOMPANYING APPLICATION PARTS

8. ☐

Assignment Papers (cover sheet & documents)

9. ☐

37 CFR 3.7(b) Statement  
(when there is an assignee)

Power of Attorney

10. ☐

English Translation Document (if applicable)

11. ☐

Information Disclosure  
Statement (IDS)/PTO-1449

Copies of IDS  
Citations

12. ☐

Preliminary Amendment

13. ☒ X

Return Receipt Postcard (MPEP 503)  
(Should be specifically itemized)

14. ☐

Small Entity  
Statement(s)

Statement filed in prior application  
Status still proper and desired

15. ☐

Certified Copy of Priority Document(s)  
(if foreign priority is claimed)

16. ☐

Other:

17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:

☐

Continuation

☐

Divisional

☐

Continuation-in-part (CIP)

of prior application No. \_\_\_\_\_

## 18. CORRESPONDENCE ADDRESS

☒ X

Customer Number or Bar Code Label

05514

(Insert Customer No. or Attach bar code label here)

or ☐

Correspondence address below

NAME

Address

City

State

Zip Code

Country

Telephone

Fax

CLAIMS	(1) FOR	(2) NUMBER FILED	(3) NUMBER EXTRA	(4) RATE	(5) CALCULATIONS
	<b>TOTAL CLAIMS</b> (37 CFR 1.16(a))	20-20 =	0	X \$ 18.00 =	\$ 00.00
	<b>INDEPENDENT CLAIMS</b> (37 CFR 1.16(b))	1-3 =	0	X \$ 78.00 =	\$ 00.00
	<b>MULTIPLE DEPENDENT CLAIMS</b> (if applicable) (37 CFR 1.16(d))			\$260.00 =	\$ 260.00
				<b>BASIC FEE</b> (37 CFR 1.18(a))	\$ 760.00
	<b>Total of above Calculations =</b>				<b>\$1020.00</b>
	<b>Reduction by 50% for filing by small entity (Note 37 CFR 1.9, 1.27, 1.28).</b>				
	<b>TOTAL =</b>				<b>\$1020.00</b>

## 19. Small entity status

- a. ☐ A Small entity statement is enclosed
- b. ☐ A small entity statement was filed in the prior nonprovisional application and such status is still proper and desired.
- c. ☐ Is no longer claimed.


20. ☒ A check in the amount of \$ 1020.00 to cover the filing fee is enclosed.

21. ☐ A check in the amount of \$ \_\_\_\_\_ to cover the recordal fee is enclosed.

22. The Commissioner is hereby authorized to credit overpayments or charge the following fees to Deposit Account No. 06-1205:

- a. ☒ Fees required under 37 CFR 1.16.
- b. ☐ Fees required under 37 CFR 1.17.
- c. ☐ Fees required under 37 CFR 1.18.

## SIGNATURE OF APPLICANT, ATTORNEY, OR AGENT REQUIRED

NAME	Scott D. Malpede, Reg. No. 32,533
SIGNATURE	
DATE	May 14, 1999

## IMAGE FORMING APPARATUS

### BACKGROUND OF THE INVENTION

#### Field of the Invention

5           The present invention relates to an image forming apparatus.

#### Related Background Art

          Flat panel image forming apparatuses, typically plasma display and liquid crystal display, are now  
10       being developed to make them thin and light in weight. A means for cooling an image display panel of such image forming apparatuses of high output and high precision has been proposed in order to prevent shortening element life due to a slow leak through a  
15       crack which would be formed without cooling, and deformation of the panel to be caused by thermal strain and to prevent a shortened lifetime to be caused by a temperature rise.

          For example, as shown in Fig. 21, in the  
20       publication of JP-A-03-196782, a heatsink plate 51 having a fin structure is mounted on the back of an image display panel 10 in order to cool the back.

          As shown in Figs. 22A and 22B, in the publication of JP-A-08-179836, a metal pipe 61 is mounted on the  
25       back of an image display panel 10 and liquid cooled with an air fan 63 and a heatsink 62 is flowed in the metal pipe.

          Also as shown in Fig. 23, in the publication of

JP-A-08-055567, air blown from a fan 71 mounted on the back of a housing 72 is guided into the inside of the housing 72 along an image display panel 10 to the front side thereof, in order to cool the whole of the panel 10.

The above-described conventional techniques are found, however, not satisfactory, because the cooling system becomes bulky as the screen size becomes large and because the depth size and consumption power of the apparatus increase.

#### SUMMARY OF THE INVENTION

It is an object of the present invention to provide an image forming apparatus having the structure capable of efficiently dissipating heat not suitable for the apparatus.

It is another object of the present invention to provide an image forming apparatus having the structure capable of making uniform the distribution of temperature in the whole of an envelope (display panel) as much as possible.

It is another object of the present invention to provide an image forming apparatus capable of forming an image having a higher quality.

In order to achieve the above objects of the invention, there is provided an image forming apparatus which has an envelope formed by first and second

substrates disposed at a predetermined distance  
therebetween and image forming means disposed in the  
envelope, wherein a heat insulating member is disposed  
on a surface of the envelope in an area excepting  
5 partial surface areas of the first and second  
substrates.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a perspective view of an image forming  
10 apparatus according to a first configuration of an  
embodiment of the invention.

Fig. 2 is a diagram showing a disassembled state  
of the image forming apparatus shown in Fig. 1.

Fig. 3 is a cross sectional view illustrating the  
15 function of the image forming apparatus shown in Fig.  
1.

Fig. 4 is a perspective view of an image forming  
apparatus according to a second configuration of an  
embodiment of the invention.

Fig. 5 is a diagram showing a disassembled state  
20 of the image forming apparatus shown in Fig. 4.

Fig. 6 is a cross sectional view illustrating the  
function of the image forming apparatus shown in Fig.  
4.

Fig. 7 is a perspective view of an image forming  
25 apparatus according to a third configuration of an  
embodiment of the invention.

Fig. 8 is a diagram showing a disassembled state of the image forming apparatus shown in Fig. 7.

Fig. 9 is a cross sectional view illustrating the function of the image forming apparatus shown in Fig.

5 7.

Fig. 10 is a perspective view of an image forming apparatus according to a fourth configuration of an embodiment of the invention.

Fig. 11 is a diagram showing a disassembled state of the image forming apparatus shown in Fig. 10.

Fig. 12 is a cross sectional view illustrating the function of the image forming apparatus shown in Fig. 10.

Fig. 13 is a perspective view of an image forming apparatus according to a third embodiment of the invention.

Fig. 14 is a cross sectional view showing an image display panel of the image forming apparatus shown in Fig. 13.

Fig. 15 is a diagram showing a disassembled state of the image forming apparatus shown in Fig. 13.

Fig. 16 is a perspective view of an image forming apparatus according of a fourth embodiment of the invention.

Fig. 17 is a cross sectional view showing an image display panel of the image forming apparatus shown in Fig. 16.

Fig. 18 is a diagram showing a disassembled state of the image forming apparatus shown in Fig. 16.

Fig. 19 is a diagram showing an example of a heat insulating member.

5        Fig. 20 is a diagram showing an example of a layout of the heat insulating member shown in Fig. 19.

Fig. 21 is a diagram showing a conventional image forming apparatus with a heat dissipation fin.

10       Figs. 22A and 22B are diagrams showing a conventional image forming apparatus utilizing coolant.

Fig. 23 is a diagram showing a conventional image forming apparatus with a fan.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

15       An image forming apparatus of this invention has an envelope formed by first and second substrates disposed at a predetermined distance therebetween and image forming means disposed in the envelope, wherein a heat insulating member is disposed on a surface of the  
20       envelope in an area excepting partial surface areas of the first and second substrates.

25       The image forming apparatus of this invention includes, for example, a liquid crystal display panel, a plasma display panel, an electron beam display panel, and the like. These image forming apparatus has image forming means disposed in its envelope.

For example, the image forming means of an

electron beam display panel includes electron emitting elements and an image forming member which forms an image when electrons from the electron emitting element are applied. The image forming member is constituted  
5 of, for example, an electrode for accelerating electrons and a light emitting member for emitting light when electrons are applied.

The envelope of an electron beam display panel is constituted of, for example, first and second  
10 substrates disposed at a predetermined distance therebetween, the first substrate being provided with electron emitting elements and the second substrate being provided with the image forming member.

The heat insulating member of the invention may be  
15 disposed directly on the side of the envelope or may be held by the housing which supports the envelope and disposed on the side of the envelope in contact with the envelope.

The image forming apparatus of the invention will  
20 be described more specifically with reference to preferred configurations of an embodiment.

Fig. 1 is a perspective view of an image forming apparatus according to the first configuration of an embodiment. In Fig. 1, reference numeral 2 represents  
25 a first substrate (hereinafter called a rear plate) mounted with electron emitting elements (not shown), and reference numeral 2 represents a second substrate



(hereinafter called a face plate) mounted with a light emitting member (not shown) on which an image is formed upon application of an electron beam emitted from an electron emitting element. The rear plate 2 and face plate 1 are disposed facing each other and fixed on a frame 3 by baking frit glass (not shown) to thereby form an envelope (hereinafter called an image display panel) 10.

Fig. 2 is a diagram showing a disassembled state of the image forming apparatus of the first configuration. In Fig. 2, reference numeral 10 represents the image display panel. A front heat insulating member 4 and a back heat insulating member 5 are mounted on the surfaces of the image display panel on the sides of the face plate 1 and rear plate 2, respectively. Side heat insulating members 6 are mounted on the side walls of the image display panel 10. Therefore, the heat insulating members are mounted on the surfaces of the image display panel 10, excepting partial surface areas 11 on the sides of the face plate 1 and rear plate 2. These areas 11 correspond to the areas where image forming means is mounted in the envelope. In this configuration of an embodiment, the area 11 corresponds to the area where the light emitting member is disposed on the inner surface of the face plate 1, and to the area where the electron emitting elements are disposed on the inner

surface of the rear plate 2. These areas 11 are hereinafter collectively called an image display area.

Next, with referent to Fig. 3, the principle of the configuration will be described. In Fig. 3, arrows indicate a heat flow.

As the image display panel 10 is driven to display an image thereon by signals supplied from an external drive circuit (not shown), the image display panel generates heat. This heat is mostly generated in the image display area 11. The generated heat is dissipated from the surface of the image display panel 10. However, since the heat insulating members 4, 5 and 6 are mounted on the whole surface excepting the image display area 11 of the image display panel 10, most of heat is dissipated from the image display area 11 on the surface of the image display panel. A portion of heat is conducted in the image display panel 10 so that the temperature of the image display panel 10 excepting the image display area 11 rises. Therefore, in a steady state, the temperature of the image display panel 10 is made uniform.

As the material of the image display panel, glass is generally used. Glass has a small thermal conductivity. A length of a heat flow in a direction perpendicular to the surface of the image display panel 10, i.e., a thickness of each of the face plate 1 and rear plate 2, is sufficiently shorter than a half of a

length of a heat flow from the central area of the image display area 11 toward the peripheral area in a direction parallel to the surface of the image forming apparatus 10, i.e., a length of the image display panel 10 in the direction parallel to the surface thereof. Therefore, even if the heat insulating members are not mounted and heat is dissipated from the whole panel surface, most of heat generated in the central area of the image display area 11 flows in the direction perpendicular to the surface of the image display panel 10. This means that a heat dissipation amount in the area excepting the image display area 11 hardly contributes to a heat dissipation amount in the central area of the image display area 11. Therefore, even if the surface excepting the image display area 11 is insulated from heat, the highest temperature of the image display panel 10 hardly changes.

Figs. 4, 5 and 6 are diagrams showing an image forming apparatus of the second configuration of an embodiment. Fig. 4 is a perspective view of the image forming apparatus of the second configuration, Fig. 5 is an assembly/disassembly diagram of the apparatus, and Fig. 6 illustrates the principle of the second configuration. In Figs. 4, 5 and 6, elements identical to those of the image forming apparatus shown in Figs. 1 to 3 are represented by identical reference numerals.

The different point of the image forming apparatus

of the second configuration from the first configuration is that a heat dissipation amount adjusting member 7 is mounted on the front surface of the rear plate 2 in area 11 where the back heat  
5 insulating member 5 is not disposed. The other structures are the same as those of the first configuration.

In the second configuration, the heat dissipation amount adjusting member 7 provides the following  
10 function in addition to the function described with reference to Fig. 3.

If there is a difference of the heat generation amount in the image display area 11, particularly  
between the face plate 1 and rear plate 2 of the image  
15 display panel 10, the heat dissipation amount adjusting member 7 disposed on the surface of the image display area 11 of the image display panel 10 on the side of the rear plate 2 adjusts the heat generation amount and reduces the temperature difference of the image display  
20 panel 10 between the face plate 1 side and rear plate 2 side. The heat dissipation amount adjusting member 7 functions as a heat insulating member if the heat generation amount of the face plate 1 is larger than that of the rear plate 2, and functions as a heat  
25 dissipating member in the contrary case. Fig. 6 illustrates an example where the heat generation amount of the face plate 1 is larger than that of the rear

plate 2. By using heat dissipating material as the material of the heat dissipation amount adjusting member 7, the heat generation amount from the rear plate 2 side of the image display panel 10 becomes  
5 small so that the temperature on the side of the rear plate 2 of the image display panel 10 rises and the temperature difference of the image display panel 10 between the face plate 1 side and rear plate 2 side reduces.

10 Figs. 7, 8 and 9 are diagrams showing an image forming apparatus of the third configuration of an embodiment. Fig. 7 is a perspective view of the image forming apparatus of the third embodiment, Fig. 8 is an assembly/disassembly diagram of the apparatus, and Fig.  
15 9 illustrates the principle of the third configuration. In Figs. 7, 8 and 9, elements identical to those of the image forming apparatus shown in Figs. 1 to 3 are represented by identical reference numerals.

The different point of the image forming apparatus  
20 of the third configuration from the first configuration is that a heat dissipation amount adjusting member 7 is mounted on the front surface of the face plate 1 in area 11 where the front heat insulating member 4 is not disposed. The other structures are the same as those  
25 of the first configuration.

In the third configuration, the heat dissipation amount adjusting member 7 provides the following

function in addition to the function described with reference to Fig. 3.

If there is a difference of the heat generation amount in the image display area 11, particularly  
5 between the face plate 1 side and rear plate 2 side of the image display panel 10, the heat dissipation amount adjusting member 7 disposed on the surface of the image display area 11 of the face plate 1 side of the image display panel 10 adjusts the heat generation amount and  
10 reduces the temperature difference between the face plate 1 side and rear plate 2 side of the image display panel 10. The heat dissipation amount adjusting member 7 functions as a heat dissipating member if the heat generation amount of the face plate 1 is larger than  
15 that of the rear plate 2, and functions as a heat insulating member in the contrary case. Fig. 9 illustrates an example where the heat generation amount of the rear plate 2 is larger than that of the face plate 1. By using heat dissipating material as the  
20 material of the heat dissipation amount adjusting member 7, the heat generation amount from the face plate 1 side of the image display panel 10 becomes small so that the temperature of the face plate 1 side of the image display panel 10 rises and the temperature  
25 difference between the face plate 1 side and rear plate 2 side of the image display panel 10 reduces.

In the first to third configurations of an

embodiment, it is more preferable that a heat conducting member is mounted between the image display panel and the heat insulating member disposed on the surface of the image display panel.

5           As an example wherein the heat conducting member is mounted, an image forming apparatus of the fourth configuration of an embodiment is used as shown in Figs. 10, 11 and 12. Fig. 10 is a perspective view of the image forming apparatus of the fourth configuration  
10           of an embodiment, Fig. 11 is an assembly/disassembly diagram of the apparatus, and Fig. 12 illustrates the principle of the fourth configuration. In Figs. 10, 11, and 12, elements identical to those of the image forming apparatus shown in Figs. 4 to 6 are represented  
15           by identical reference numerals.

          The different points of the image forming apparatus of the fourth configuration from the second configuration are that a front heat insulating member 4 is mounted via a front heat conducting member 8 on the  
20           surface of the face plate 1 side and that a back heat insulating member 5 is mounted via a back heat conducting member 9 on the surface of the rear plate 2 side. The other structures are the same as those of the second configuration.

25           In the fourth configuration, the heat conducting member 8 and 9 provide the following function in addition to the function described with reference to

Fig. 3 and 6.

Since the heat insulating members 4, 5 and 6 are disposed on the whole surface excepting the image display area 11 of the image display panel 10, most of heat dissipation is from the image display area 11 of the image display panel 10. A portion of heat thermally conducts in the image display panel so that the temperature in the area other than the image display area 11 rises. In this case, as shown in Fig. 12, the thermal conduction is performed efficiently by the heat conducting members 8 and 9 so that a delay of the temperature rise in a transient state until the temperature of the image display panel enters the steady state, can be alleviated.

In the first to fourth configurations described above, it is possible to considerably suppress an uneven temperature distribution on the surface of the image display panel to be caused by heat generation in the image display area, i.e., to considerably reduce a temperature difference between the inner and outer areas of the image display area of the image display panel and a temperature difference between the face plate side and rear plate side of the image display panel to be caused by a difference between heat generation amounts. Accordingly, thermal strain of the image display panel to be caused by the temperature differences can be removed as much as possible.



In the first to fourth configurations described above, as the material of the heat insulating member, material is used which has a thermal conductivity smaller than the material of the surface layer of the image display panel. For example, for an image display panel made of glass, the material may be glass wool, ceramic fiber, urethane foam or the like.

In the above configurations, the front heat insulating member 4, back heat insulating member 5 and four side heat insulating members 6 are discrete members. However, they may be integrally formed by using urethane foam or the like, or may be a structure having small rooms partitioned so as not to allow natural convection, or a vacuum envelope. A thickness of the heat insulating member is suitably designed, desirably 1 to 30 mm.

Also in the above configurations, as the material of the heat conducting member, material is used which has a thermal conductivity larger than that of the surface layer of the material of the image display panel. For example, for an image display panel made of glass, the material may be metal such as aluminum, silver, copper and platinum, or alumina. The shape may be a sheet shape, or the heat conducting member may be integrally formed with the plated member or heat insulating film on the surface of the image display panel.

Also in the above configurations, as the material of the heat dissipating member, material is used which has a thermal conductivity larger than that of the surface layer of the material of the image display panel. For example, for an image display panel made of glass, the heat dissipating member may be a metal plate having a fin structure, a metal flat plate, a fin structure made of alumina, a flat plate made of alumina, or the like. Cooling means may be provided by mounting a water cooling pipe on a heat dissipating plate and flowing liquid therein.

(First Embodiment)

An image forming apparatus was manufactured having the above-described configuration and a matrix type electron source substrate with surface conduction type electron emitting elements. This embodiment will be described by referring again to Figs. 10 and 11.

Reference numeral 10 represents an image display panel which is constituted of a face plate 1 provided with fluorescent body, a rear plate 2 provided with the plural electron emitting elements, a frame 3 all made of soda-lime glass. The thicknesses of the face plate 1 and rear plate 2 were both 2.8 mm and a thickness of the frame 3 was 3 mm. The thermal conductivities of the face plate 1, rear plate 2 and frame 3 were all about 0.7 W/mK. A front heat conducting member 8 and a back heat conducting member 9 made of an aluminum sheet

of 200  $\mu\text{m}$  in thickness were mounted as a heat conducting means on the face plate 1 and rear plate 2 in an area excepting the image display area 11 of the image display panel 10. Thereafter, a front heat  
5 insulating member 4 and a back heat insulating member 5 of glass wool were mounted as a heat insulating means. Four side heat insulating members 6 of glass wool were mounted as a heat insulating means on the side walls of the image display panel 10 as shown in Fig. 11.

10 Although it is more preferable that each heat insulating member is thicker, the thickness is determined in accordance with a space in the envelope. In this embodiment, a thickness of 10 to 30 mm was set. As a means for adjusting a difference of the heat  
15 generation amount between the face plate 1 and rear plate 2, a heat dissipation amount adjusting member 7 of glass wool was mounted on the back surface of the rear plate 2 side in the image display area 11. A thickness of the heat dissipation amount adjusting  
20 member 7 is set properly in accordance with an output power when an image is displayed. The thermal conductivities of the front heat insulating member 4, back heat insulating member 5 and heat dissipation amount adjusting member 7 were 0.05 W/mK.

25 An image was displayed on the image forming apparatus by supplying a drive signal from an external drive circuit. In the image display panel, the crack

which would cause slow leak to shorten the element life was not formed, even the image was displayed for a long time, and a color shift was not observed in the image.

Thermal strain to be generated in the image  
5 display panel was simulated with a computer. The thermal strain was reduced by 31 % if the thickness of the heat insulating member was 10 mm, and by 48 % if it was 30 mm.

A maximum temperature rise in the image display  
10 panel occurred in the central area of the image display area. This occurred in the central area both for the thicknesses of 10 mm and 30 mm of the heat insulating member when an image was displayed on each image display panel.  
15 (Second Embodiment)

An image forming apparatus was manufactured having the above-described configuration and a matrix type electron source substrate with surface conduction type electron emitting elements.

20 Fig. 4 is a perspective view showing the structure of the image forming apparatus of this embodiment, and Fig. 5 is an assembly/disassembly diagram of the image forming apparatus. With reference to Figs. 4 and 5, this structure of this embodiment will be described.

25 Reference numeral 10 represents an image display panel which is constituted of a face plate 1 provided with fluorescent body, a rear plate 2 provided with the

plural electron emitting elements, a frame 3 all made of soda-lime glass similar to the first embodiment. The thicknesses of the face plate 1 and rear plate 2 were both 2.8 mm and a thickness of the frame 3 was 3 mm. A front heat insulating member 4 and a back heat insulating member 5 made of glass wool similar to the first embodiment were mounted as a heat insulating means on the surfaces of the face plate 1 side and rear plate 2 side of the image display panel 10 in the area other than the image display area 11. Four side heat insulating members 6 of glass wool similar to the first embodiment were mounted as a heat insulating means on the side walls of the image display panel 10 as shown in Fig. 5. Although it is more preferable that each heat insulating member is thicker, the thickness is determined in accordance with a space in the envelope. In this embodiment, a thickness of 10 to 30 mm was set. As a means for adjusting a difference of the heat generation amount between the face plate 1 and rear plate 2, a heat dissipation amount adjusting member 7 of glass wall similar to the first embodiment was mounted on the back surface side of the rear plate 2 in the image display area 11. A thickness of the heat dissipation amount adjusting member 7 is set properly in accordance with an output power when an image is displayed.

An image was displayed on the image forming

apparatus by supplying a drive signal from an external drive circuit. In the image display panel, any undesirable crack was not formed, even the image was displayed for a long time, and a color shift was not  
5 observed in the image.

Thermal strain to be generated in the image display panel was simulated with a computer. The thermal strain was reduced by 11 % if the thickness of the heat insulating member was 10 mm, and by 23 % if it  
10 was 30 mm.

A maximum temperature rise in the image display panel occurred in the central area of the image display area. This occurred in the central area both for the thicknesses of 10 mm and 30 mm of the heat insulating  
15 member when an image was displayed on each image display panel.

(Third Embodiment)

In this embodiment, the invention is applied to an image forming apparatus in which an amount of heat  
20 generation from the side of the rear plate formed with electron emitting elements is larger than an amount of heat generation from the side of the face plate mounted with a light emitting member and a temperature on the rear plate side is higher than a temperature on the  
25 face plate side.

Figs. 13, 14 and 15 are diagrams illustrating this embodiment. Fig. 13 is a perspective view partially

broken of the image forming apparatus, Fig. 14 is a cross sectional view of an image display panel, and Fig. 15 is an assembly/disassembly view of the image forming apparatus.

5 First, the image display panel will be described with reference to Fig. 14. Reference numeral 102 represents a rear plate on which a plurality of electron emitting elements 301 are mounted. Reference numeral 101 represents a face plate on which a light  
10 emitting member 302 is mounted for radiating light and forming an image when an electron beam emitted from the electron emitting element and accelerated is applied. Reference numeral 103 represents a frame, and reference numeral 110 represents an image display panel which is  
15 formed by mounting the face plate 101 and rear plate 102 on the frame 103 and fixing them by baking frit glass (not shown). In this embodiment, the electron emitting element is a surface conduction type electron emitting element. The image display panel having the  
20 above-described structure can be manufactured by using techniques disclosed and detailed, for example, in JP-A-07-235255. The details thereof are omitted herein. Wiring leads and atmospheric resistant support members are omitted and not shown.

25 The face plate 101, rear plate 102 and frame 103 are made of soda-lime glass (3 mm in thickness) having a thermal conductivity of about 0.7 W/mK.

Reference numeral 111 represents an image display area on the side of the face plate 101 which area on the face plate faces the light emitting member 302. In the image display area 111, a heat flow caused by an electron beam application to the light emitting member 302 is directed in the image display area 111 in the +Z direction.

Reference numeral 112 represents an image display area on the side of the rear plate 102 which area on the rear plate faces the electron emitting elements 301. In the image display area 112, a heat flow from the electron emitting elements 301 is directed in the -Z direction.

The image display areas 111 and 112 have approximately the same size.

Next, with reference to Fig. 13, the structure of the image forming apparatus will be described.

Reference numeral 110 represents the image display panel which is constituted of the face plate 101, rear plate 102 and frame 103 as described with reference to Fig. 14. Reference numeral 104 represents a front heat isolating member made of a heat insulating board having a thickness of 20 mm, with an area corresponding to the image display area 111 being punched out. The heat insulating member 104 is made of the material whose main components are fibers of silica-alumina raw material, and has a thermal conductivity of about 0.07



W/mK. Reference numeral 108 represents a front thermal conducting member disposed between the face plate 101 and front heat insulating member 104 in an outer area relative to the image display area 111 on the side of  
5 the face plate 101, and made of a graphite sheet having a thickness of 0.05 mm. The thermal conductivity of the graphite sheet is about 200 W/mK.

Reference numeral 105 represents a back heat insulating member made of the same heat insulating  
10 board as the front heat insulating member 104, with an area corresponding to the image display area 112 being punched out. Reference numeral 109 represents a back heat conducting member disposed between the rear plate 102 and back heat insulating member 105 in an outer  
15 area relative to the image display area 112 on the side of the rear plate 102. The thermal conductivity of the aluminum alloy sheet is about 120 W/mK.

Reference numeral 106 represents a side heat insulating member made of a heat insulating board (same  
20 material as the heat insulating boards 104 and 105) having an outer size larger than that of the image display panel 110 by 40 mm and a thickness of 5 mm, with an area corresponding to the image display panel 110 being punched out to form a frame having a width of  
25 20 mm.

Reference numeral 113 represents a transparent heat insulating film disposed in an outer area (in the

+Z direction) relative to the image display area on the side of the face plate 101. The heat insulating film 113 is made of a polyethylene terephthalate (PET) film having a thickness of 0.2 mm, a thermal conductivity of about 0.3 W/mK and a visible light transmittance of about 98 %. The heat insulating film 113 functions as a heat dissipation amount adjusting member. Although the thickness of this film 113 is thin as different from the other heat insulating members, the thickness corresponds to about 0.5 mm as converted into a thermal thickness of soda-lime glass, and provides a sufficient heat insulating effect.

Reference numeral 114 represents a heatsink plate having a fin for enhancing heat dissipation. The heatsink plate 114 is mounted on an outer area (-Z direction) relative to the image display area 112 on the side of the rear plate 102 by using a both-side thermal conductive tape. The heatsink plate 114 is made of magnesium alloy having a thermal conductivity of about 50 W/mK. The heatsink plate 114 with the fin was integrally manufactured by a die-cast method. The heatsink plate 114 with the fin functions as a heat dissipation adjusting member. Heat dissipation was conducted through natural convection.

If the heatsink plate 114 with the fin becomes in contact with the back heat conducting member 109, the temperature of the back heat conducting member 109

lowers. It is therefore preferable to provide a space of about 1 mm to 30 mm between the heatsink plate 114 with the fin and the back heat conducting member.

Next, an assembly method for the image forming apparatus will be described with reference to Fig. 15. First, the heat insulating film 113 is adhered to the image display area 111 of the outer face of the face plate 101 by using achromatic and transparent acrylic adhesive (about 25  $\mu\text{m}$  thick). Next, on the front heat insulating member 104, the front heat conducting member 108 and side heat insulating member 106 are sequentially mounted, and the image display panel 110 is fitted into an opening of the side heat insulating member 106. Then, the back heat conducting member 109 is mounted in an outer area relative to the image display area 112 on the outer side of the rear plate 102, and the back heat insulating member 105 is mounted. Next, the heatsink plate 114 with the fin is adhered to the image display area 112 on the side of the rear plate 102 by using a both-side thermal conductive tape (not shown) to complete the assembly.

The heat insulating members are fixed together by adhesive (not shown). Since the adhesive between the heat insulating members provides a heat insulating effect, the adhesive is selected by taking preference of a fixing strength. The thermal conductivity of the acrylic adhesive is 0.1 to 0.5 W/mK and the thickness

thereof is 25  $\mu\text{m}$ , so that this acrylic adhesive plays a partial roll of the heat insulating effect of the heat insulating film 113.

An image was displayed on the image forming  
5 apparatus assembled in the above manner by supplying  
image signals from an external drive circuit. A  
temperature of the apparatus was measured with a  
thermoviewer (infrared thermometer) and a thermocouple,  
a thermal strain was measured with a strain gage, and a  
10 pixel color shift was observed with a magnifying lens.  
A temperature difference of the outer surface of the  
image display panel was 3°C or smaller, and the thermal  
strain was 1 MPa which was in a measurement error  
range. A color shift of an image to be caused by a  
15 thermal expansion difference between the face plate 101  
and rear plate 102 was not observed.

In this embodiment, with respect to the +Z  
direction of the image display panel, the temperature  
of the image display area 111 in an outer area (+Z  
20 direction) relative to the face plate 101 rose because  
of the heat insulating film 113, whereas the  
temperature of the image display area 112 in an outer  
area (-Z direction) relative to the rear plate 102  
lowered because of the heatsink plate 114. The  
25 temperatures of the face plate 101 and rear plate 102  
were therefore able to be made generally equal and  
there was no temperature difference between the front

and back of the image display panel. As a result, a color shift of an image to be caused by a warp of the image display panel resulting from thermal expansion was not observed.

5           Also in this embodiment, with respect to the in-plane direction (plane perpendicular to the Z-axis) of the image display panel, a temperature difference in the in-plane was reduced because of front, back and side heat insulating members. The thermal strain (stress) at an area (low temperature area) where thermal strain was generated conventionally was in a measurement error range and sufficiently reduced. As a result, vacuum slow leak from cracks to be caused by thermal strain was not observed, and the image forming apparatus was able to be driven stably for a long time.

10           In this embodiment, silica-alumina material is used as the material of the heat insulating board. A heat insulating board made of glass wool, rock wool or the like was used and same advantages as above were obtained.

15           Cooling by the heatsink plate with the fin is conducted by natural convection. Instead, the fin may not be used if the heat generation amount of the rear plate 102 is slightly larger than that of the face plate 101, whereas if the heat generation amount of the rear plate 102 is much larger than that of the face plate 101, it is preferable to cool the heatsink 114

with the fin through forced air cooling.

Although magnesium alloy is used as the material of the heatsink plate 114 with the fin, metal or metal alloy may also be used. Non-metallic material such as alumina having a higher thermal conductivity than glass may be used or the fin may be formed through a cutting work, with similar advantages described above.

In this embodiment, although the heatsink 114 with the fin is manufactured by a die-cast method, it may be formed by a thixo-mold method.

(Fourth Embodiment)

In this embodiment, the invention is applied to an image forming apparatus in which an amount of heat generation from the side of the rear plate formed with electron emitting elements is smaller than an amount of heat generation from the side of the face plate mounted with a light emitting member and a temperature on the face plate side is higher than a temperature on the rear plate side.

Figs. 16, 17 and 18 are diagrams illustrating this embodiment. Fig. 16 is a perspective view partially broken of the image forming apparatus, Fig. 17 is a cross sectional view of an image display panel, and Fig. 18 is an assembly/disassembly view of the image forming apparatus.

First, the image display panel will be described with reference to Fig. 17. Reference numeral 202

represents a rear plate on which a plurality of electron emitting elements 301 are mounted. Reference numeral 201 represents a face plate on which a light emitting member 302 is mounted for radiating light and forming an image when an electron beam emitted from the electron emitting element and accelerated is applied. Reference numeral 203 represents a frame, and reference numeral 210 represents an image display panel which is formed by mounting the face plate 201 and rear plate 202 on the frame 203 and fixing them by baking frit glass (not shown). In this embodiment, the electron emitting element is a surface conduction type electron emitting element. The image display panel having the above-described structure can be manufactured by using techniques disclosed and detailed, for example, in JP-A-07-235255. The details thereof are omitted herein. Wiring leads and atmospheric resistant support members are omitted and not shown.

The face plate 201, rear plate 202 and frame 203 are made of soda-lime glass (3 mm in thickness) having a thermal conductivity of about 0.7 W/mK.

Reference numeral 211 represents an image display area on the side of the face plate 201 which area on the face plate faces the light emitting member 302. In the image display area 211, a heat flow caused by an electron beam application to the light emitting member 302 is directed in the image display area 211 in the +Z

direction.

Reference numeral 212 represents an image display area on the side of the rear plate 202 which area on the rear plate faces the electron emitting elements 301. In the image display area 212, a heat flow from the electron emitting elements 301 is directed in the -Z direction.

The image display areas 211 and 212 have approximately the same size.

Next, with reference to Fig. 16, the structure of the image forming apparatus will be described. Reference numeral 210 represents the image display panel which is constituted of the face plate 201, rear plate 202 and frame 203 as described with reference to Fig. 17. Reference numeral 204 represents a front/side heat insulating member made of urethane foam material which is formed by integrally molding a front heat insulating member and a side heat insulating member. The thickness is 3 mm. The heat insulating member 204 has an opening in an area corresponding to the image display area 211. The thermal conductivity of the urethane foam material is about 0.04 W/mK. Reference numeral 208 represents an aluminum sheet having a thickness of 50  $\mu$ m adhered and fixed to the surface of the heat insulating member 204 on the side of the face plate 201 by using adhesive. Since the adhesive between the heat insulating members provides a heat



insulating effect, the adhesive is selected in view of preference of a fixing strength.

Reference numeral 205 represents a back heat insulating member made of the same heat insulating board as the heat insulating member 204, with an area  
5 corresponding to the image display area 212 being punched out. Reference numeral 209 represents a back heat conducting member disposed between the rear plate 202 and back heat insulating member 205, and adhered  
10 and fixed to the surface of the back heat insulating member 20 on the side of the rear plate 202, the back heat conducting member 209 being made of an aluminum sheet having a thickness of 50  $\mu$ m.

Reference numeral 214 represents a heat insulating sheet disposed in an outer area (-Z direction) relative  
15 to the image display area 212 on the side of the rear plate 202. The heat insulating sheet 214 has a thickness of 0.4 mm and is made of the material having as its main components fibers of a high alumina  
20 material. The heat insulating sheet 214 can raise the temperature of the rear plate 202.

Next, an assembly method for the image forming apparatus will be described with reference to Fig. 18. First, the image display panel 210 is fitted into the  
25 opening of the integrally formed heat insulating member 204 and front heat conducting member 208. Then, the back heat insulating member 205 with the adhered back

heat conducting member 209 is mounted. Next, the heat insulating sheet 214 is adhered to the image display area 212 on the side of the rear plate 202 by using adhesive (not shown) to complete the assembly. The heat insulating members are fixed together by adhesive (not shown). It is more preferable to tightly adhere the heat insulating sheet 214 and back heat insulating member 205, because the heat insulating effect is improved.

An image was displayed on the image forming apparatus assembled in the above manner by supplying image signals from an external drive circuit. An image was not degraded by vacuum slow leak to be caused by thermal strain even if the apparatus was operated for a long time, and a color shift of an image to be caused by a thermal expansion difference between the face plate 201 and rear plate 202 was not observed.

In this embodiment, with respect to the +Z direction of the image display panel, the temperature of the image display area 212 in an outer area (-Z direction) relative to the rear plate 201 rose because of the heat insulating film 214, and the temperatures of the face plate 201 and rear plate 202 were able to be made generally equal and there was no temperature difference between the front and back of the image display panel. As a result, a color shift of an image to be caused by a warp of the image display panel

resulting from thermal expansion was not observed.

Also in this embodiment, with respect to the in-plane direction (plane perpendicular to the Z-axis) of the image display panel, a temperature difference in the in-plane was reduced because of front, back and side heat insulating members. The thermal strain (stress) at an area (low temperature area) where thermal strain was generated conventionally was in a measurement error range and sufficiently reduced. As a result, vacuum slow leak from cracks to be caused by thermal strain was not observed, and the image forming apparatus was able to be driven stably for a long time.

In this embodiment, urethane foam material is used as the material of the heat insulating board. A mold of fine ceramics may be used as the heat insulating board. In this case, for example, aluminum was vapor deposited on the surface of the mold to form the front heat conductive member, with similar advantages described above.

In the first to fourth embodiments described above, the heat insulating effect can be improved by executing particularly the following process for the surface of the heat insulating member. With an improved heat insulating effect, the thickness of the heat insulating member can be made as thin as 2 to 5 mm and the image forming apparatus can be made more thinner.

This process will be described specifically by using as an example the heat insulating member 204 of the fourth embodiment.

Fig. 19 is an enlarged perspective view showing a portion of the heat insulating member 204, and Fig. 20 is an enlarged cross sectional view thereof. In Figs. 19 and 20, reference numeral 221 represents a surface of the heat insulating member 204 on the side (-Z direction) of the face plate 201, reference numeral 222 represents a semispherical adiabatic space formed in the surface layer of the heat insulating member 204, and reference numeral 223 represents a through hole formed in the front heat conducting member 208 at the position same as that of the adiabatic space. The diameter of the semispherical adiabatic space and that of the through hole 223 are the same. Reference numeral 201 represents the face plate.

For the assembly, the front heat conducting member 208 is adhered and fixed to the molded heat insulating member 204, with the adiabatic spaces 223 being aligned with the through holes 223, and the heat insulating member 204 with the front heat conductive member 208 is pressed against the face plate 201.

By spatially restricting a motion of air (thermal conductivity of 0.01 W/mK) in the adiabatic space 222, the heat insulating effect can be improved considerably.

Instead of the semispherical shape of the adiabatic space 222, a circular hole, a rectangular hole, a groove or the like may be used so long as the motion of air which provides the heat insulating effect can be spatially restricted.

If the work cost of the through holes 223 to be formed in the front heat conducting member 208 becomes high or if a manufacture yield is lowered because of a positioning failure of the through holes 223 and adiabatic spaces 222 at the assembly stage, then the effects of the through holes 223 are not utilized satisfactorily and it is preferable not to form through holes from the viewpoint of manufacture cost.

According to the present invention, it is possible to provide an image forming apparatus having the structure capable of efficiently dissipating heat not suitable for the apparatus.

Further, according to the present invention, it is possible to provide an image forming apparatus having the structure capable of making uniform the distribution of temperature in the whole of an envelope (display panel) as much as possible.

Furthermore, according to the present invention, it is possible to provide an image forming apparatus capable of forming an image having a higher quality.

WHAT IS CLAIMED IS:

1. An image forming apparatus having an envelope formed by first and second substrates disposed at a predetermined distance therebetween and image forming means disposed in the envelope, wherein:

a heat insulating member is disposed on a surface of the envelope in an area excepting partial surface areas of the first and second substrates.

2. An image forming apparatus according to claim 1, wherein the image forming means comprises electron emitting elements disposed on the first substrate and an image forming member disposed on the second substrate for forming an image when electrons emitted from the electron emitting element are applied.

3. An image forming apparatus according to claim 2, wherein said heat insulating member is disposed on the surface of the envelope in an area excepting the partial surface area of the second substrate.

4. An image forming apparatus according to claim 2, wherein said heat insulating member is disposed on the surface of the envelope in an area excepting the partial surface area of the first substrate.

5. An image forming apparatus according to claim

2, wherein said heat insulating member is disposed on the surface of the envelope in an area excepting the partial surface areas of the first and second substrates.

5

6. An image forming apparatus according to any one of claims 1 to 5, further comprising heat dissipating means disposed in the partial surface area.

10

7. An image forming apparatus according to any one of claims 1 to 5, further comprising a heat conducting member between the surface of the envelope and said heat insulating member.

15

8. An image forming apparatus according to any one of claims 1 to 5, wherein said heat insulating member has a thickness in a range from 1 mm to 30 mm.

ABSTRACT OF THE DISCLOSURE

An image forming apparatus having an envelope formed by first and second substrates disposed at a predetermined distance therebetween and image forming means disposed in the envelope, wherein a heat insulating member is disposed on a surface of the envelope in an area excepting partial surface areas of the first and second substrates.

10



**FIG. 1**





FIG. 2







**FIG. 3**




FIG. 5



**FIG. 6**

**FIG. 7**

**FIG. 8**




**FIG. 9**

FIG. 10




FIG. 11







FIG. 12





**FIG. 13**

**FIG. 14**


+Z ← → -Z

FIG. 15



**FIG. 16**



**FIG. 17**



**FIG. 18**

FIG. 19





**FIG. 20****FIG. 21**

FIG. 22A




FIG. 22B





FIG. 23



COMBINED DECLARATION AND POWER OF ATTORNEY  
FOR PATENT APPLICATION

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name;

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled IMAGE FORMING APPARATUS

the specification of which ☒ is attached hereto ☐ was filed on \_\_\_\_\_ as United States Application No. or PCT International Application No. \_\_\_\_\_ and was amended on \_\_\_\_\_ (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR §1.56.

I hereby claim foreign priority benefits under 35 U.S.C. §119(a)-(d) or §365(b), of any foreign application(s) for patent or inventor's certificate, or §365(a) of any PCT international application which designates at least one country other than the United States, listed below and have also identified below any foreign application for patent or inventor's certificate, or PCT international application having a filing date before that of the application on which priority is claimed:

Country	Application No.	Filed (Day/Mo./Yr.)	Priority Claimed (Yes/No)
Japan	10-136693	19/May/1998	Yes

I hereby claim the benefit under 35 U.S.C. § 120 of any United States application(s), or §365(c) of any PCT international application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT international application in the manner provided by the first paragraph of 35 U.S.C. § 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 C.F.R. § 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

Application No.	Filed (Day/Mo./Yr.)	Status (Patented, Pending, Abandoned)
-----------------	---------------------	--

I hereby appoint the practitioners associated with the firm and Customer Number provided below to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith, and direct that all correspondence be addressed to the address associated with that Customer Number:

**FITZPATRICK, CELLA, HARPER & SCINTO**  
Customer Number: 05514

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full Name of Sole or First Inventor JUNICHI SEKI

Inventor's signature \_\_\_\_\_

Date \_\_\_\_\_ Citizen/Subject of JAPAN

Residence 6-29, Mizuhiki 2-chome, Atsugi-shi, Kanagawa-ken, Japan

Post Office Address c/o CANON KABUSHIKI KAISHA, 30-2, Shimomaruko 3-chome, Ohta-ku, Tokyo, Japan